

BAILOUT REGULATORS & GAUGES

Professional Grade Diving Equipment

Apeks DST & DS4 1st Stage Regulators





- · Robust and field-proven design
- Ideal for Surface-Supplied bailout or SCUBA use
- Excellent performance in all conditions and temperatures
- Apeks Dry Sealed (DS) environmental sealing system
- · Balanced, over-tracking design
- Available with Yoke (A-clamp) or DIN (300 bar) fittings
- Suitable for immediate use with EAN mixtures to 40% O2
- O2 compatible versions available
- · Adjustable Pressure Relief Valve (APRV) available

DST (Dry Seal Turret) - swivel turret with 2 x HP, 4 x MP ports DS4 (Dry Seal 4-Port) - 1 x HP port, 4 x MP ports

CE Standard EN 250 certified to 165 fsw (50 msw) for open circuit and cold water diving NORSOK Standard U101 certified to 656 fsw (200 msw) for heliox/mixed gas diving

Adjustable Pressure Relief Valve

- · Fully-adjustable relief valve
- Prevents gas hose from rupturing if 1st stage fails
- Recommended safety fitting for all diving operations
- · Low profile prevents damage and snagging
- Suitable for any 1st stage diving regulator
- Adjustable 175 245 psi (12 17 bar)
- Factory preset to 217 psi (15 bar)
- Chrome-plated brass construction
- O2 compatible version available



Part #
AP0527
AP0528
AP0361
AP0361-1
AP0849
102810
AP6101
AP0633IMP
AP0635IMP





DS4 Yoke

DS4 DIN





DST Yoke

DST DIN

Submersible Mini-Gauges

- Suitable for any 1st stage diving regulator
- · Low profile prevents damage and snagging
- 2 versions: 0-3000 psi or 0-350 bar



Mini-Gauges psi / bar

Pressure Gauge & Hose

- Submersible Pressure Gauge (SPG) w/ Hose
- · Dial range: 0-5000 psi
- Slim line case made from nickel plated brass
- Anti-splinter polycarbonate dial window
- · Built-in over pressure relief

